



FEATURES


- Miniature SIP package
- Efficiency up to 89%
- High power density
- 3000VDC isolation
- Operating temperature range:
-40°C ~ +105°C
- No external component required
- Industry standard pinout
- continuous short circuit protection

DEZ_S2P & DFZ_S2P Series

2W, FIXED INPUT, ISOLATED & UNREGULATED DUAL/SINGLE OUTPUT DC-DC CONVERTER

PART NUMBER SYSTEM

DEZ-0505-S2P



APPLICATIONS

The DEZ_S2P & DFZ_S2P Series are designed for application where isolated output is required for application where isolated output is required from a distributed power system.

These products apply to where:

- 1) Input voltage variationrang:±10% Vin;
- 2) 3000VDC input and output isolation;
- 3) Regulated and low ripple noise is not required.

Such as: digital circuits, low frequency analog circuits and relay drive circuits.

SELECTION GUIDE

Model	Input Voltage(VDC)	Output Voltage (VDC)	Output Current (mA)		Input Current (mA)(typ.)		Reflected Ripple Current (mA,typ.)	Max. Capacitive Load ^① (μF)	Efficiency (% , typ.) @Max. Load
	Nominal (Range)		Max.	Min.	@Max. Load	@No Load			
DEZ-0505-S2P	5 (4.5-5.5)	±5	±200	±20	476	25	10	100	80
DEZ-0512-S2P		±12	±83.3	±8.3	476				84
DEZ-0515-S2P		±15	±66.6	±6.7	476				84
DEZ-0524-S2P		±24	±41.6	±4.2	476				84
DFZ-0505-S2P		5	400	40	450			220	89
DFZ-0512-S2P		12	166.6	16.6	476				84
DFZ-0515-S2P		15	133.3	13.3	476				84
DFZ-0524-S2P		24	83.3	8.3	476				84
DEZ-1205-S2P	12 (10.8-13.2)	±5	±200	±20	198	15	5	100	84
DEZ-1212-S2P		±12	±83.3	±8.3	196				85
DEZ-1215-S2P		±15	±66.6	±6.7	198				84
DFZ-1205-S2P		5	400	40	198			220	84
DFZ-1212-S2P		12	166.6	16.6	198				84
DFZ-1215-S2P		15	133.3	13.3	198				84
DEZ-1515-S2P	15 (13.5-16.5)	±15	±66.6	±6.7	157	10	5	100	85
DEZ-2405-S2P	24 (21.6-26.4)	±5	±200	±20	99	8			84
DEZ-2412-S2P		±12	±83.3	±8.3	99				84
DEZ-2415-S2P		±15	±66.6	±6.7	99				84
DFZ-2405-S2P		5	400	40	99			220	84
DFZ-2412-S2P		12	166.6	16.6	99				84
DFZ-2415-S2P		15	133.3	13.3	99				84
DFZ-2424-S2P		24	83.3	8.3	98				85

Note: ① For dual output converter, the given value is the same for each output.

INPUT SPECIFICATIONS

Item	Test Conditions	Min.	Typ.	Max.	Unit
Input Surge Voltage (1sec. Max.)	5VDC Input	-0.7	--	9	VDC
	12VDC Input	-0.7	--	18	
	15VDC Input	-0.7	--	21	
	24VDC Input	-0.7	--	30	
Input Filter		Capacitance			

OUTPUT SPECIFICATIONS

Item	Test Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy			See tolerance envelope curve			
Line Voltage Regulation	For Vin change of ±1%		--	--	±1.2	%
Load Regulation	10% to 100% load	5VDC output	--	10	--	
		12VDC output	--	8	--	
		15VDC output	--	7	--	
		24VDC output	--	6	--	
Temperature coefficient	100% load		--	--	±0.03	%/°C
Ripple & Noise*	20MHz Bandwidth	Output Voltage ≤12VDC	--	60	--	mVp-p
		Output Voltage: 15VDC, 24VDC	--	75	--	
Short Circuit Protection			Continuous, automatic recovery			

Note: * Ripple and noise tested with "parallel cable" method. See detailed operation instructions at *DC-DC Application Notes*.

COMMON SPECIFICATIONS

Item	Test Conditions	Min.	Typ.	Max.	Unit
Isolation Voltage	Input-Output, Tested for 1 minute and leakage current less than 1 mA	3000	--	--	VDC
Isolation Resistance	Input-Output, Test at 500VDC	1000	--	--	M Ω
Isolation Capacitance	Input-Output, 100KHz/0.1V	DEZ-2415-S2P/DFZ-2424-S2P	--	30	pF
		Others	--	20	
Switching Frequency	Full load, nominal input	--	100	300	KHz
MTBF	MIL-HDBK-217F@25 $^{\circ}\text{C}$	3500	--	--	K hours
Case Material	Plastic (UL94-V0)				
Weight		--	2.4	--	g

ENVIRONMENTAL SPECIFICATIONS

Item	Test Conditions	Min.	Typ.	Max.	Unit
Storage Humidity	Non condensing	--	--	95	%
Operating Temperature	Power derating (≥ 85°C, see figure 2)	-40	--	105	°C
Storage Temperature		-55	--	125	
Temp. rise	Ta=25°C,100% Load	--	25	--	
Lead Temperature	1.5mm from case for 10 seconds	--	--	300	
Cooling		Free air convection			


EMC SPECIFICATIONS

EMI	CE	CISPR22/EN55022 CLASS B (Typical Recommended Circuit Refer to Figure1)			
	RE	CISPR22/EN55022 CLASS B (Typical Recommended Circuit Refer to Figure1)			
EMS	ESD	DEZ_S2P	IEC/EN61000-4-2 Contact $\pm 6\text{KV}$ perf. Criteria B		
		DFZ_S2P	IEC/EN61000-4-2 Contact $\pm 8\text{KV}$ perf. Criteria B		

The models listed above is just for standard type. If you need the special specification product, please contact our service member by telephone presented in shortform cover or e-mail to : info@zimtec-electronics.de

EMC RECOMMENDED CIRCUIT

EMI Typical Recommended Circuit (CLASS B):




(Figure 1)

Note: If there is no recommended parameters, the model no require the external component.


Recommended typical circuit parameters:

Vin(V)		5	12/15/24
EMI	C1	4.7 μ F /50V	4.7 μ F /50V
	C2	--	470pF/3KV
	LDM	6.8 μ H	6.8 μ H


EMC TEST WAVEFORM (CLASS B APPLY CIRCUIT)




DEZ-2415-S2P CE(Positive Line)



DFZ-2405-S2P CE(Positive Line)




DEZ-2415-S2P CE(Negative Line)




DFZ-2405-S2P CE(Negative Line)

PRODUCT TYPICAL CURVE

Tolerance Envelope Curve




Temperature Derating Graph




(Figure 2)



Efficiency VS Input Voltage curve
(Full Load)



Efficiency VS Output Load curve
(Vin=Vin-nominal)




The models listed above is just for standard type. If you need the special specification product, please contact our service member by telephone presented in shortform cover or e-mail to : info@zimtec-electronics.de



OUTLINE DIMENSIONS, RECOMMENDED FOOTPRINT & PACKAGING

MECHANICAL DIMENSIONS





PIN CONNECTION		
Pin	Single	Dual
1	Vin	Vin
2	GND	GND
5	0V	-Vo
6	No Pin	0V
7	+Vo	+Vo

Note:
 Unit :mm[inch]
 Pin section tolerances:±0.1mm[±0.004inch]
 General tolerances:±0.25mm[±0.010inch]


THIRD ANGLE
 PROJECTION

RECOMMENDED FOOTPRINT DETAILS



Note : Grid 2.54*2.54mm

TUBE PACKAGING DIMENSIONS




Note:
 Unit:mm[inch]
 General tolerances:±0.50mm[±0.020inch]
 L=530mm[20.866inch] Tube Quantity:25 pcs
 L=220mm[8.661inch] Tube Quantity:10 pcs
 Inner carton(S): L*W*H=255*170*80 mm
 Outer carton(S): L*W*H=375*280*270mm, 6 inner cartons(S);
 Inner carton(L): L*W*H=580*200*100mm;
 Outer carton(L): L*W*H=600*215*220mm, 2 inner cartons(L);
 Outer carton(L): L*W*H=600*215*325mm, 3 inner cartons(L);

TEST CONFIGURATIONS

Input Reflected-Ripple Current Test Setup

Input reflected-ripple current is measured with an inductor Lin and Capacitor Cin to simulate source impedance.



DESIGN CONSIDERATIONS

1) Requirement for output load

To ensure this module can operate efficiently and reliably, the minimum output load could not be less than 10% of the full load. If the actual output power is very small, please connect a resistor to the output in parallel to increase the load.


2) Overload Protection

Under normal operating conditions, the output circuit of these products have not overload protection. The simplest method is to add a breaker circuit in the circuit.

3) Recommended circuit

If you want to further decrease the input/output ripple, an capacitor filtering network may be connected to the input and output ends of the DC/DC converter, refer to Figure 3.

It should also be noted that the capacitance of the capacitor must be proper. If the capacitance is too large a startup problem might arise. For ensuring every channel of output can provide a safe and reliable operation, the recommended capacitance of the capacitor refer to Table 1.



(Figure 3)


EXTERNAL CAPACITOR TABLE (Table 1)

Vin (VDC)	Cin (μF)	Single Vo (VDC)	Cout (μF)	Dual Vo (VDC)	Cout# (μF)
5	4.7	5	10	±5	4.7
12	2.2	12	2.2	±12	1
15	2.2	15/24	1	±15/±24	0.47
24	1	--	--	--	--

It's not recommended to connect any external capacitor in the application field with less than 0.5 watt output.

4) Output Voltage Regulation and Over voltage Protection Circuit

The simplest device for output voltage regulation, over-voltage and over-current protection is a linear regulator with overheat protection which is connected to the input or output in series (Figure 4) and an capacitor filtering network. the recommended capacitance of the capacitor refer to Table 1, linear regulator based on the actual voltage and current to make a reasonable selection.



(Figure 4)

5) It is not recommended to increase the output power capability by connecting two or more converters in parallel. The product is not hot-swappable

Note:

1. Operation under minimum load will not damage the converter; However, they may not meet all specifications.
2. Max. Capacitive Load is tested at nominal input voltage and full load.
3. Unless otherwise noted, All specifications are measured at Ta=25°C, humidity<75%, nominal input voltage and rated output load.
4. In this datasheet, all test methods are based on our corporate standards.
5. All characteristics are for listed models, and non-standard models may perform differently. Please contact our technical support for more detail.
6. Please contact our technical support for any specific requirement.
7. Specifications of this product are subject to changes without prior notice.