

DJ-3W Series

3W 4:1 Regulated Single & Dual output

Features

- Wide 4:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation, Up to 3500 VDC
- Continuous Short Circuit Protection
- Efficiency up to 80%
- -40 ~ 85°C Operation Temperature Range
- Metal Case Standard, Optional Plastic Case



The DJ series is a family of cost effective 3W single & dual output DC-DC converters. These converters are consisted with Nickle-coated copper in a 24-pin DIL package with high performance features such as 1500 VDC ~ 3500VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 24 and 48 with output voltage of 3.3, 5, 9, 12, 15, 24, ± 3.3 , ± 5 , ± 9 , ± 12 , ± 15 and ± 24 Vdc. High performance features include high efficiency operation up to 80% and output voltage accuracy of $\pm 1\%$ maximum.

All specifications typical at Ta=25°C, nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$
Line regulation	$\pm 0.5\%$
Load regulation	$\pm 0.5\%$
	(Output 3.3V / ± 3.3 V Model) $\pm 1.5\%$
Ripple & noise (20 MHz bandwidth)(1)	60mV pk-pk
Short circuit protection	Indefinite(Automatic Recovery)
Temperature coefficient	$\pm 0.02\%/^{\circ}\text{C}$
Capacitor load(2)	See table

INPUT SPECIFICATIONS	
Voltage Range	See table
Max. Input Current	See table
No-Load Input Current	See table
Input Filter	PI Type
Input Reflected Ripple Current (3)	35mA pk-pk

GENERAL SPECIFICATIONS	
Efficiency	See table, typ
I/O Isolation Voltage(3 sec)	
Input/Output	1500~3500Vdc
Metal Case/Input & Output	1000Vdc
I/O Isolation Capacitance	470 pF Typ.
I/O Isolation Resistance	1000M Ohm
Switching Frequency	Typical 266kHz
Humidity	95% rel H
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121 Mhrs
Safety Standard : (designed to meet)	IEC 60950-1



PHYSICAL SPECIFICATIONS	
Case Material	Nickel-coated Copper
	Non-conductive Black Plastic(UL94V-0 rated)
Base Material	Non-conductive Black Plastic(UL94V-0 rated)
Pin Material	0.5mm Brass Solder-coated
Potting Material	Epoxy (UL94V-0 rated)
Weight	17.0g (Metal Case)/ 13.5g(Plastic Case)
Dimensions	1.25 "x0.8 "x0.4 "

ENVIRONMENT SPECIFICATIONS	
Operating Temperature	-40 °C~85 °C(See Derating Curve)
Maximum Case Temperature	100 °C
Storage Temperature	-40 °C~125 °C
Cooling	Nature Convection

ABSOLUTE MAXIMUM RATINGS(4)	
These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Input Surge Voltage(100mS)	
24 Models	40 Vdc max.
48 Models	80 Vdc max.
Soldering Temperature	260 °C max.
(1.5mm from case 10 sec. max.)	

DJ - 3W 4:1 Regulated Single & Dual output

PART NUMBER STRUCTURE



MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
DJ-243R3S3	9-36	16	165	3.3	0	900	75	680
DJ-2405S3	9-36	16	160.3	5	0	600	78	470
DJ-2409S3	9-36	16	156.3	9	0	333	80	100
DJ-2412S3	9-36	16	156.3	12	0	250	80	68
DJ-2415S3	9-36	16	156.3	15	0	200	80	47
DJ-2424S3	9-36	16	156.3	24	0	125	80	22
DJ-243R3D3	9-36	16	165	±3.3	0	±454	75	±330
DJ-2405D3	9-36	16	160.3	±5	0	±300	78	±220
DJ-2409D3	9-36	16	156.3	±9	0	±166	80	±47
DJ-2412D3	9-36	16	156.3	±12	0	±125	80	±33
DJ-2415D3	9-36	16	156.3	±15	0	±100	80	±22
DJ-2424D3	9-36	16	156.3	±24	0	±63	80	±10
DJ-483R3S3	18-72	14	82.5	3.3	0	900	75	680
DJ-4805S3	18-72	14	80.1	5	0	600	78	470
DJ-4809S3	18-72	14	78.1	9	0	333	80	100
DJ-4812S3	18-72	14	78.1	12	0	250	80	68
DJ-4815S3	18-72	14	78.1	15	0	200	80	47
DJ-4824S3	18-72	14	78.1	24	0	125	80	22
DJ-483R3D3	18-72	14	83.3	±3.3	0	±454	75	±330
DJ-4805D3	18-72	14	80.1	±5	0	±300	78	±220
DJ-4809D3	18-72	14	78.1	±9	0	±166	80	±47
DJ-4812D3	18-72	14	78.1	±12	0	±125	80	±33
DJ-4815D3	18-72	14	78.1	±15	0	±100	80	±22
DJ-4824D3	18-72	14	78.1	±24	0	±63	80	±10

Suffix "H" means 3.5KVdc isolation

Suffix "P" means Plastic case instead of standard Metal Case


NOTE

1. Ripple/Noise measured with a 1uF ceramic capacitor.
2. Test by nominal input voltage and constant resistor load.
3. Measured Input reflected ripple current with a simulated source inductance of 12uH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.

TEST CONFIGURATIONS


Input Reflected Ripple Current Test Step

Input reflected ripple current is measured through a source inductor L_{in} (12uH) and a source capacitor C_{in} (47uF, ESR<1.0Ω at 100KHz) at nominal input and full load.




Output Ripple & Noise Measurement Test


Use a capacitor C_{out} (1.0uF) measurement. The Scope measurement bandwidth is 0-20MHz.



ELECTRICAL CHARACTERISTIC CURVES




24 Models



48 Models


MECHANICAL SPECIFICATIONS



PIN CONNECTIONS		
PIN NUMBER	SINGLE	DUAL
1	+V Input	+V Input
2	+V Input	+V Input
10	N.C.	Com mon
11	N.C.	Com mon
12	-V Output	N.C.
13	+V Output	-V Output
15	N.C.	+V Output
23	-V In put	-V In put
24	-V In put	-V In put

(The Pin Connection of high isolation one is the same with normal one.)

MECHANICAL SPECIFICATIONS



PIN CONNECTIONS		
PIN NUMBER	SINGLE	DUAL
1	+V Input	+V Input
2	+V Input	+V Input
10	N.C.	Com mon
11	N.C.	Com mon
12	-V Output	N.C.
13	+V Output	-V Output
15	N.C.	+V Output
23	-V In put	-V In put
24	-V In put	-V In put